

Safety Data Sheet

R32

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: R-32
OTHER NAME: Difluoromethane
USE: Refrigerant Gas
STORAGE: ICOOL USA INCORPORATED
 1638 Thompson Rd SE
 Hartselle, AL 35640

FOR MORE INFORMATION CALL: (Monday-Friday, 8:00am-5:00pm) 1-256-754-5507
IN CASE OF EMERGENCY CALL: CHEMTREC: 1-800-424-9300

2. HAZARDS IDENTIFICATION



CLASSIFICATION: Gases under pressure, Liquefied Gas, Flammable Gas
SIGNAL WORD: DANGER
HAZARD STATEMENT: Extremely flammable gas, contains gas under pressure, may explode if heated
SYMBOL: Gas Cylinder, Flame
PRECAUTIONARY STATEMENT: Prevention: Keep away from heat, sparks, open flame, and hot surfaces. No Smoking
 Response: Leaking gas fire: Do not extinguish unless leak can be stopped immediately. Eliminate all ignition sources if safe to do so.
 Storage: Protect from sunlight, store in a well-ventilated place.

EMERGENCY OVERVIEW: Flammable gas. Liquid under high pressure. Colorless, volatile liquid with ethereal and faint sweetish odor. Non-flammable material. Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result from exposure. Vapors displace air and can cause asphyxiation in confined spaces. At higher temperatures, (>250°C), decomposition products may include Hydrofluoric Acid (HF) and carbonyl halides.

POTENTIAL HEALTH HAZARDS

SKIN: Irritation would result from a defatting action on tissue. Liquid contact could cause frostbite.
EYES: Liquid contact can cause severe irritation and frostbite. Mist may cause irritation.

INHALATION: R-32 is low in acute toxicity in animals. When oxygen levels in air are reduced to 12-14% by displacement, symptoms of asphyxiation, loss of coordination, increased pulse rate and deeper respiration will occur. At high levels, cardiac arrhythmia may occur.

INGESTION: Ingestion is unlikely because of the low boiling point of the material. Should it occur, discomfort in the gastrointestinal tract from rapid evaporation of the material and consequent evolution of gas would result. Some effects of inhalation and skin exposure would be expected.

DELAYED EFFECTS: None known.

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS NUMBER	WEIGHT %
Difluoromethane	75-10-5	100

COMMON NAME and SYNONYMS

R-32; HFC32

There are no impurities or stabilizers that contribute to the classification of the material identified in Section 2

4. FIRST AID MEASURES

SKIN: Promptly flush skin with water until all chemical is removed. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. Get medical attention if symptoms persist.

EYES: Immediately flush eyes with large amounts of water for at least 15 minutes (in case of frostbite water should be lukewarm, not hot) lifting eyelids occasionally to facilitate irrigation. Get medical attention if symptoms persist.

INHALATION: Immediately remove to fresh air. If breathing has stopped, give artificial respiration. Use oxygen as required, provided a qualified operator is available. Get medical attention. Do not give epinephrine (adrenaline).

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

ADVICE TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: Not applicable

AUTOIGNITION TEMPERATURE: Not available

UPPER FLAME LIMIT: 31% (% v/v)

LOWER FLAME LIMIT: 14% (% v/v)

HAZARDOUS REACTIONS:

Reacts with finely divided metals such as aluminum, zinc, magnesium, and alloys containing more than 2% magnesium. Can react violently if in contact with alkali metals and alkaline earth metals such as sodium, potassium, or barium.

During a fire the product can form toxic and corrosive gases such as hydrogen fluoride.

EXTINGUISHING MEDIA:

Suitable extinguishing medium is dry powder. Allow escaping gas to urn under controlled conditions. Extinguish only if escape of gas can be rapidly stopped as it may form a flammable vapor cloud.

FIRE AND EXPLOSION HAZARDS:

Flammable liquefied gas. Container may burst under intense heat. Ruptured cylinders may rocket or fragment. Heavy vapor may suffocate.

Certain mixtures of HFC-32 and chlorine may be flammable under some conditions.

FIRE FIGHTING PROCEDURES:

Water spray should be used to cool containers.

FIRE FIGHTING PROTECTIVE EQUIPMENT:

Use self-contained breathing apparatus with a full-face piece and special protective clothing.

6. ACCIDENTAL RELEASE MEASURES

IN CASE OF SPILL OR OTHER RELEASE: (Always wear recommended personal protective equipment.)

This product is a flammable, liquefied gas, which exits the container at temperatures capable of causing freeze burns (frostbite). Contents under pressure. Ruptured cylinder may rocket or fragment.

Precautions should take into account the severity of the leak or spill.

Move unprotected personnel upwind of leaking container. Remove ignition sources and ventilate the spill area. Use recommended personal protection and shut off the leak, if without risk. If possible, elevate leak position to highest point of container (should leak gas, not liquid). Water should never be put on leak nor should cylinder be immersed. If possible, dike

and contain spillage. Prevent liquid from entering sewers sumps, or pit areas since vapor is heavier than air and can create a suffocation atmosphere. Capture material for recycle or destruction if suitable equipment is available.

Notify applicable government authority if release is reportable or could adversely affect the environment.

7. HANDLING AND STORAGE

HANDLING:

Wear appropriate personal protective equipment. A safety shower and eyewash station should be nearby and ready for use.

This product is a flammable, liquefied gas, which exits the container at temperatures capable of causing freeze burns (frostbite). Ensure personnel are trained in handling and storing cylinders. Secure containers at all times. Keep containers closed when not in use.

Ensure there is adequate ventilation or use proper respiratory protection in poorly ventilated or confined areas. Avoid causing and inhaling high concentration or vapor. Atmospheric levels should be controlled to below the occupational exposure limit and kept as low as practicable.

Prevent liquid or vapor from entering sumps or sewers since vapor is heavier than air and may form suffocating atmospheres.

Do not put mixtures of HFC-32 with air or oxygen under pressure; do not use such mixtures for leak or pressure testing. Do not heat containers.

Liquid transfers between containers may generate static electricity. Ensure adequate grounding.

Avoid trapping liquid between closed valves or overfilling containers as high pressures can develop with an increase in temperature.

Avoid HFC-32 contact with flames or very hot surfaces.

STORAGE RECOMMENDATIONS:

Keep containers tightly closed, in a cool, well-ventilated place. Keep containers dry. Keep from incompatibles, open flames, hot surfaces, welding operations, and other heat sources.

STORAGE TEMPERATURE:

Store at temperature not exceeding 125 deg. F. (52deg. C).

INCOMPATIBILITIES:

Freshly abraded aluminum surfaces at specific temperatures and pressures may cause a strong exothermic reaction. Chemically reactive metals: potassium, calcium, powdered aluminum, magnesium, and zinc.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Use ventilation to maintain safe levels. Where appropriate engineering controls are not in place or are inadequate, wear suitable respiratory equipment.

PERSONAL PROTECTIVE EQUIPMENT

SKIN PROTECTION:

Take all precautions to prevent skin contact. Use gloves and protective clothing made of material that has been found by user to be impervious under conditions of use to prevent the skin from becoming frozen for contact with liquid. User should verify impermeability under normal conditions of use prior to general use. Additional protection such as an apron, arm covers, or full body suit may be needed depending on conditions of use.

EYE PROTECTION:

Use chemical safety goggles or safety glasses and a face shield when there is potential for eye contact.

RESPIRATORY PROTECTION:

Not normally needed if controls are adequate. If needed, use NIOSH/MSHA approved respirator for organic vapors. For high concentrations and oxygen-deficient atmospheres, use positive pressure air-supplied respirator.

OTHER PROTECTION:

Shower and eye wash station.

EXPOSURE GUIDELINES

<u>INGREDIENT NAME</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER LIMIT</u>
Difluoromethane	None	None	*1000 ppm TWA (8hr)

* = Workplace Environmental Exposure Level (AIHA)

Minimize exposure in accordance with good hygiene practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:

Colorless liquefied gas
Gas at ambient temperature

PHYSICAL STATE:

ODOR:	Faint ethereal odor
SOLUBILITY IN WATER (weight %):	Insoluble
BOILING POINT:	-51.7°C (-61.1°F)
VAPOR PRESSURE (mmHg at 20 deg. C):	10,319
FLASH POINT:	>662F (ASTM-D-1929 Method B)
EVAPORATION RATE	Not Available
FLAMMABILITY:	Mildly flammable
LEL/UFL:	14.4% / 31%
PARTITION COEFF (n-octanol/water)	Log Pow: 0.21. Note: This product is more soluble than octanol
AUTO IGNITION TEMP:	648°C / 198°F
DECOMPOSITION TEMPERATURE:	No data available
VISCOSITY:	Not applicable
VAPOR DENSITY (air = 1.0):	1.86 at normal boiling point
% VOLATILES BY VOLUME	100 WT%
DENSITY:	0.96 g/cm ³ at 77F (25°C)
pH:	Not applicable
MELTING POINT:	-280°F
SPECIFIC GRAVITY (water = 1.0):	0.98 at 68F (20°C)
MOLECULAR FORMULA:	CH ₂ F ₂
MOLECULAR WEIGHT:	50.02

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:

Stable under normal conditions.

INCOMPATIBILITIES:

Reacts with finely divided metals such as aluminum, zinc, magnesium, and alloys containing more than 2% magnesium. Can react violently if in contact with alkali metals and alkaline earth metals such as sodium, potassium, or barium.

HAZARDOUS DECOMPOSITION PRODUCTS:

Hydrogen fluoride by thermal decomposition and hydrolysis.

CONDITIONS TO AVOID:

Keep away from heat, sparks, and flame. Avoid high temperatures.

HAZARDOUS POLYMERIZATION:

Will not occur.

11. TOXICOLOGICAL INFORMATION

POSSIBLE HUMAN HEALTH EFFECTS:**Routes of Exposure:**

Inhalation, ingestion, eye, and skin contact.

Inhalation: Exposure to high vapor concentrations may cause an abnormal heart rhythm and prove suddenly fatal. Very high atmospheric concentrations can cause anesthetic effects progressing from dizziness, weakness, nausea, to unconsciousness. It can act as an asphyxiant by limiting available oxygen.

Ingestion: Highly unlikely, but should this occur, freeze burns will result.

Eye Contact: Liquid splashes or spray may cause freeze burns. **Skin Contact:** Liquid splashes or spray may cause freeze burns.

Other Effects: None anticipated.

Carcinogenicity:

<u>Ingredient Name</u>	<u>NTP STATUS</u>	<u>ACGIH</u>	<u>IARC STATUS</u>	<u>OSHA LIST</u>
------------------------	-------------------	--------------	--------------------	------------------

No ingredients listed in this section

ANIMAL DATA:

LC50 4 hr., (rat inhalation) - > 520,000 ppm

Because of its volatility this compound has not been tested for skin or eye irritancy or skin sensitization.

No cardiac sensitization (arrhythmias) occurred in dogs pretreated with epinephrine at 350,000 ppm. In an earlier cardiac sensitization study, a no observed effect level (NOEL) of 200,000 ppm and threshold of 250,000 ppm were established.

No teratogenic effects were seen in rats or rabbits at dose levels up to 50,000 ppm.

No adverse effects were seen at the highest dose level of 50,000 ppm in a 90-day inhalation.

No genotoxicity was observed in a range of in vitro tests or an in vivo mouse micronucleus assay.

12. ECOLOGICAL INFORMATION

Degradability (BOD): R-32 is a gas at room temperature; therefore, it is unlikely to remain in water.

Octanol Water Partition Coefficient: Log P_{ow} = 0.21 (difluoromethane)

PERSISTENCE AND DEGRADATION:

Decomposes comparatively rapidly in the lower atmosphere (troposphere). Atmospheric lifetime is 4.9 years. Products of decomposition will be highly dispersed and hence will have a very low concentration. It is not considered an ozone-depleting chemical.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD:

Discarded product is not a hazardous waste under RCRA, 40 CFR 261. However, HFC-32 should be recycled, reclaimed, or destroyed whenever possible.

CONTAINER DISPOSAL:

May contain explosive vapors. Do not distribute, make available, furnish, or reuse container when emptied of the original product. Do not weld or use cutting torch on or near container. Empty container retains product residue. Return containers to supplier.

REFRIGERATION APPLICATION:

Subject to "no venting" regulations of Section 608 of the Clean Air Act during the service or disposal of equipment.

14. TRANSPORT INFORMATION

US DOT ID NUMBER: UN3252

US DOT HAZARD CLASS: US DOT PROPER SHIPPING NAME: Difluoromethane or Refrigerant gas R-32
US DOT HAZARD CLASS: 2.1

US DOT PACKING GROUP: Not applicable

15. REGULATORY INFORMATION

TSCA (TOXIC SUBSTANCES CONTROL ACT) REGULATIONS, 40 CFR 710: All ingredients are on the TSCA Chemical Substances Inventory.

CERCLA and SARA REGULATIONS:

40 CFR 372: This product does not contain any chemicals subject to reporting requirements of SARA Section 313.

40 CFR 355: This product does not contain any "extremely hazardous chemical" subject to the requirements of SARA Section 312.

40 CFR 370: Hazardous properties as defined under the Hazard Communication Standard (29 CFR 1910.1200).

Health: Acute effects (CNS depression, cardiac sensitization).

Physical: Flammable liquefied gas.

(Actions may be necessary under SARA Section 311 - consult regulations for applicability).

16. OTHER INFORMATION

CURRENT ISSUE DATE: September, 2018

PREVIOUS ISSUE DATE: -

OTHER INFORMATION:

HMIS Classification: Health - 1, Flammability - 4, Reactivity - 1

NFPA Classification: Health - 2, Flammability - 4, Reactivity - 1

Regulatory Standards:

1. OSHA regulations for compressed gases: 29 CFR 1910.101
2. DOT classification per 49 CFR 172.101

DISCLAIMER:

ICOOL USA INC. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods or use of the product and of the information referred to herein are beyond the control of ICOOL USA INC. ICOOL USA expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.